


Issue 07/12	<b>Technical Data</b>	
<b>HÜDIG piston pump</b>		<b>HÜDIG®</b>
<b>HC 271</b>		<a href="http://www.huedig.de">www.huedig.de</a>



### Design:

- Mounted on skid with oil-leakage-cover
- Fuel tank capacity 142 l (sufficient for 1 week continuous operation<sup>1)</sup>)

### Special features

- Extended oil change intervals by enlarged oil sump
- Less maintenance ratio by solid design
- Automatic lubrication system
- Oversized bearings
- Low piston speed
- Sea and brackish water durable
- Less transport costs by compact design
- Optimal access by maximised doors and easy removable cover
- Two units stackable
- Exterior frame construction protects against impacts

### Applications

Construction Industry – Municipality – Dewatering

- Wellpoint dewatering
- Drain sock dewatering

### Operation

A diesel driven double acting piston pump provides a continuous delivery of the water-air-mixture. A safe and quick suction and a constant flow rate is assured by this system.

Type	Water pump			Motor				Shipping data	
	Capacity $V_{max}$ m <sup>3</sup> /h	Connection DN <sub>S</sub> DN <sub>D</sub> mm	N°. lifts max. n 1/min	Brand	Type	Power	RPM	Lengthxwidthxheight l x b x h mm	Weight m kg
						P	n		
						kW	1/min		
HC 271/11	70	108	55	Hatz	1D81Z	6,0	1600	2200 x 1050 x 1668	1620

<sup>1)</sup> under standard conditions

Subject to change without notice!

## HÜDIG - your partner to solve water problems.

**HÜDIG®**  
GmbH & Co. KG

**Absenk- und Beregnungsanlagen**

Heinrich-Hüdig-Straße 2 · 29227 Celle  
Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18  
e-mail: [Info@huedig.de](mailto:Info@huedig.de)